

防爆合格证 Electrical Apparatus for Explosive Atmospheres

CERTIFICATE OF CONFORMITY

Manufacturer

Sun Yeh Electrical Ind. Co., Ltd.

Address: No.68, Lane 854, Sec. 1, Shatian Rd., Dadu District, Taichung City, 432,

Taiwan

Product

Explosion-proof Quarter-Turn Actuators

Type

国家防爆

OME-0-0-0

Marking

Ex db IIB T4 Gb, Ex tb IIIC T130℃ Db

Standard(s)

Drawing No.

Ex10032, Ex10036, Ex10043, Ex10044, Ex10047, Ex10048, Ex10049, Ex10050,

Ex10051

The drawings, technical documents and the samples are verified and certified according to standard(s) for safety as below:

GB/T3836.1-2021

Explosive atmospheres - Part 1: Equipment - General requirements

GB/T3836.2-2021

Explosive atmospheres - Part 2:Equipment protection by flameproof

enclosures "d"

GB/T3836.31-2021

Explosive atmospheres - Part 31:Equipment dust ignition protection by

enclosure "t"

Note:

See Annex (1 pages in total).

Director

母星

Date:

Valid until:

2022-09-14

2027-09-13



南阳防爆电气研究所

NANYANG EXPLOSION PROTECTED ELECTRICAL APPARATUS RESEARCH INSTITUTE

国家防爆电气产品质量检验检测中心

CHINA NATIONAL QUALITY SERVEY AND TEST CENTEN FOR EXPLOSION PROTECTED ELECTRICAL PRODUCTS
Address No. 20 (North Zhongjing Rd, Nanyang Henan 473008), P.R. China
Tei:037 6 32 864 Fax:0377 6 3208175 Vely wy china-ex.com





Electrical Apparatus for Explosive Atmospheres

CERTIFICATE OF CONFORMITY

Page 1 of 1

1.This product has been certified, under certificate number IECEx SIR 17.0062X, issue 3, dated 2022-06-28.

2.Type designation:

国家防爆

OME-1-a-a-a, OME-A-a-a-a, OME-AM-a-a, OME-2-a-a, OME-3-a-a,

OME-4-a-a, OME-5-a-a, OME-6-a-a, OME-7-a-a, OME-8-a-a-a

ОМ	E	_	0	 0	_		-	0
1	2		3	4		(5)		6

- ①Stands for Quarter-Turn Actuator
- 2 Stands for Explosion-proof
- 3 Stands for type (1, A, AM, 2, 3, 4, 5, 6, 7, 8)
- 4 Stands for voltage (D12 stands for 12V DC,12 stands for 12V AC, D24 stands for 24V DC, 24 stands for 24V AC, 100 stands for 100V AC, 120 stands for 110~120V AC, 200 stands for 200V AC, 220 stands for 220~240V AC)
- ⑤Stands for controlling method (M stands for Modulating, F stands for Floating)
- @Duty rating: 30, 75

3.Voltage: 12V DC, 24V DC, 12V AC, 24V AC, 100V AC, 110~120V AC, 200V AC, 220~240V AC

4.Frequency: 50/60Hz

5.Max. Torque: 35Nm, 50Nm, 90Nm, 150Nm, 400Nm, 500Nm, 650Nm, 1000Nm, 1500Nm

6.IP Degree:

Models	IP Degree IP66/IP68(72h, 7m)		
OME-1, O			
OME-2-□-□,	OME-3-0-0,	OME-4-0-0,	7 3 7 7 7 7
OME-5-□-□-□,	IP68(72h, 7m)		
OME-8-0-0			

7. Specific conditions of safety use:

1) Ambient temperature: -30°C~+70°C.

2) The flamepaths in this equipment are different to the standard dimensions given in GB/T 3836.2. If specific flamepath dimensions are required then the manufacturer (OEM) must be contacted.

3) Caution - Use fasteners with yield stress \geq 450MPa.

Director

Date:

2022-09-14

Valid until:

2027-09-13



南阳防爆电气研究所

NANYANG EXPLOSION PROTECTED ELECTRICAL APPARATUS RESEARCH INSTITUTE

国家防爆电气产品质量检验检测中心

CHINA NATIONAL QUALITY SURVEY AND TEST CENTER FOR EXPLOSION PROTECTED ELECTRICAL PRODUCTS
Address No. 20 (30th Zhongjing Rd, Nanyang Manany 473008), P.R. China
Tel: 0371 63158564 Fax: 0377 63208175 Web: w. w.china-ex.com

注:本证书仅对与认可文件和样品一致的产品有效。

登录网站或关注公众号查询真伪