

# SE

SERIES

## Explosion-proof Spring Return Fail-safe Electric Valve Actuator

Service Unique Nice Youthful Energy Honesty

# SUNYEH

## Electrical Data



SUN YEH ELECTRICAL IND. CO., LTD.

SY08-G001D-EN

## **Content**

1.	SE-500 to 2600, 1PH, 50% duty cycle .....	1
1.1	24VAC/DC, ON/OFF Control, 50% duty cycle .....	1
1.2	110-120VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle .....	1
1.3	220-240VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle .....	1
2.	SE-500 to 2600, 3PH, 50% duty cycle .....	2
2.1	220-240VAC, ON/OFF Control, 50% duty cycle .....	2
2.2	380VAC, ON/OFF Control, 50% duty cycle .....	2
2.3	440VAC, ON/OFF Control, 50% duty cycle .....	2

**1. SE-500 to 2600, 1PH, 50% duty cycle**

**1.1 24VAC/DC, ON/OFF Control, 50% duty cycle**

Model	Torque		Motor Power W	Running Current DC / 60 / 50Hz	Running Time DC / 60 / 50Hz	Return Time	Lock Current DC / 60 / 50Hz
	Nm	in-lb		Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	445	50	3.4 / 4.2 / 4.1	7 / 7 / 9	3	12.0 / 10.4 / 10.0
SE-1300	130	1150	130	7.3 / 10.0 / 10.1	8 / 7 / 8	8	20.5 / 17.5 / 17.2
SE-2000	200	1770	130	6.3 / 8.6 / 8.6	11 / 11 / 13	12	20.9 / 17.6 / 17.3
SE-2600	260	2300	130	7.3 / 10.2 / 10.2	17 / 14 / 17	12	20.9 / 17.6 / 17.3

- The running current is measured at max torque.

**1.2 110-120VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle**

Model	Torque		Motor Power W	Running Current 60 / 50Hz	Running Time 60 / 50Hz	Return Time	Lock Current 60 / 50Hz
	Nm	in-lb		Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	445	50	1.2 / 1.5	7 / 9	3	1.6 / 1.9
SE-1300	130	1150	130	4.3 / 7.2	7 / 8	8	11.5 / 12.0
SE-2000	200	1770	130	4.9 / 7.7	11 / 13	12	11.6 / 12.6
SE-2600	260	2300	130	4.0 / 7.3	14 / 17	12	11.6 / 12.6

- The running current is measured at max torque.

**1.3 220-240VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle**

Model	Torque		Motor Power W	Running Current 60 / 50Hz	Running Time 60 / 50Hz	Return Time	Lock Current 60 / 50Hz
	Nm	in-lb		Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	445	50	0.8 / 0.8	7 / 9	3	0.8 / 0.9
SE-1300	130	1150	130	2.1 / 3.6	7 / 8	8	5.5 / 6.0
SE-2000	200	1770	130	2.2 / 3.8	11 / 13	12	5.9 / 6.2
SE-2600	260	2300	130	2.5 / 3.8	14 / 17	12	5.9 / 6.2

- The running current is measured at max torque.

**2. SE-500 to 2600, 3PH, 50% duty cycle**

**2.1 220-240VAC, ON/OFF Control, 50% duty cycle**

Model	Torque		Motor Power W	Running Current 60 / 50Hz	Running Time 60 / 50Hz	Return Time Sec / 90°	Lock Current 60 / 50Hz
	Nm	in-lb		Amp	Sec / 90°		Amp
SE-500	50	443	50	0.8 / 0.8	7 / 9	3	0.8 / 0.9
SE-1300	130	1151	130	2.1 / 3.6	7 / 8	8	5.5 / 6.0
SE-2000	200	1771	130	2.2 / 3.8	11 / 13	12	5.9 / 6.2
SE-2600	260	2302	130	2.5 / 3.8	14 / 17	12	5.9 / 6.2

- The running current is measured at max torque.

**2.2 380VAC, ON/OFF Control, 50% duty cycle**

Model	Torque		Motor Power W	Running Current 60 / 50Hz	Running Time 60 / 50Hz	Return Time Sec / 90°	Lock Current 60 / 50Hz
	Nm	in-lb		Amp	Sec / 90°		Amp
SE-500	50	443	50	0.5 / 0.6	7 / 9	3	0.5 / 0.7
SE-1300	130	1151	130	1.3 / 1.7	7 / 8	8	2.6 / 2.7
SE-2000	200	1771	130	0.8 / 1.0	11 / 13	12	1.9 / 2.0
SE-2600	260	2302	130	0.8 / 1.1	14 / 17	12	1.9 / 2.0

- The running current is measured at max torque.

**2.3 440VAC, ON/OFF Control, 50% duty cycle**

Model	Torque		Motor Power W	Running Current 60 / 50Hz	Running Time 60 / 50Hz	Return Time Sec / 90°	Lock Current 60 / 50Hz
	Nm	in-lb		Amp	Sec / 90°		Amp
SE-500	50	443	50	0.3 / 0.4	7 / 9	3	0.4 / 0.5
SE-1300	130	1151	130	0.9 / 1.3	7 / 8	8	2.2 / 2.3
SE-2000	200	1771	130	0.9 / 1.4	11 / 13	12	2.2 / 2.2
SE-2600	260	2302	130	0.9 / 1.2	14 / 17	12	2.2 / 2.2

- The running current is measured at max torque.



**SUN YEH ELECTRICAL IND. CO., LTD.**

---

No.68, Ln. 854, Sec. 1, Shatian Rd., Dadu Dist.,  
Taichung City 432403, Taiwan  
Tel: +886-4-26985666 Fax: +886-4-26983668  
E-mail: [service@sunyeh.com](mailto:service@sunyeh.com)



[www.sunyeh.com](http://www.sunyeh.com)