

OME

SERIES

**Explosion-proof
Quarter-turn**

Electric Valve Actuator

SUNYEH

Electrical Data



SUN YEH ELECTRICAL IND. CO., LTD.

SY07-GA02A1-EN

Content

1.	OME-1 to 8, 1PH, 30% & 75% duty cycle	1
1.1	12VDC, Floating Control, 75% duty cycle	1
1.2	24VAC/DC, Floating Control, 75% duty cycle.....	1
1.3	24VAC/DC, Modulating Control, 75% duty cycle	2
1.4	110 - 120VAC, Floating Control, 75% duty cycle	2
1.5	110 - 120VAC, Modulating Control, 75% duty cycle	3
1.6	110 - 120VAC, Floating Control, 30% duty cycle	3
1.7	110 - 120VAC, Modulating Control, 30% duty cycle	4
1.8	220 - 240VAC, Floating Control, 75% Duty cycle	4
1.9	220 - 240VAC, Modulating Control, 75% Duty cycle	5
1.10	220 - 240VAC, Floating Control, 30% Duty cycle	5
1.11	220 - 240VAC, Modulating Control, 30% Duty cycle	6

Explosion-proof Quarter-turn Electric Valve Actuator Electrical Data

1. OME-1 to 8, 1PH, 30% & 75% duty cycle

1.1 12VDC, Floating Control, 75% duty cycle

Model	Torque		Motor Power	Power Consumption	Running Current	Running Time	Lock Current
	Nm	in-lb	W	DC / 60 / 50 Hz W	DC / 60 / 50 Hz Amp	DC / 60 / 50 Hz Sec / 90°	DC / 60 / 50 Hz Amp
OME-1	35	310	10	35 / - / -	2.9 / - / -	22 / - / -	3.1 / - / -
OME-A / AM	50	445	10	30 / - / -	2.5 / - / -	34 / - / -	3.1 / - / -
OME-2	90	800	40	53 / - / -	4.4 / - / -	15 / - / -	17.5 / - / -
OME-3	150	1330	40	62 / - / -	5.1 / - / -	24 / - / -	17.5 / - / -
OME-4	400	3540	80	170 / - / -	14.1 / - / -	21 / - / -	40.6 / - / -
OME-5	500	4430	80	174 / - / -	14.5 / - / -	29 / - / -	40.6 / - / -
OME-6	650	5755	80	262 / - / -	21.8 / - / -	35 / - / -	40.6 / - / -
OME-7	1000	8855	120	209 / - / -	17.4 / - / -	31 / - / -	72.2 / - / -
OME-8	1500	13280	120	304 / - / -	25.3 / - / -	36 / - / -	72.2 / - / -

- The running current is measured at max torque.

1.2 24VAC/DC, Floating Control, 75% duty cycle

Model	Torque		Motor Power	Power Consumption	Running Current	Running Time	Lock Current
	Nm	in-lb	W	DC / 60 / 50 Hz W	DC / 60 / 50 Hz Amp	DC / 60 / 50 Hz Sec / 90°	DC / 60 / 50 Hz Amp
OME-1	35	310	10	36 / 44 / 44	1.5 / 1.9 / 1.9	11 / 14 / 14	2.6 / 2.5 / 2.5
OME-A / AM	50	445	10	32 / 37 / 37	1.3 / 1.6 / 1.6	21 / 24 / 25	2.6 / 2.5 / 2.5
OME-2	90	800	40	46 / 76 / 75	1.9 / 3.4 / 3.4	19 / 15 / 15	14.1 / 10.4 / 10.4
OME-3	150	1330	40	65 / 80 / 87	2.7 / 3.6 / 3.9	30 / 24 / 24	14.1 / 10.4 / 10.4
OME-4	400	3540	80	178 / 211 / 203	7.4 / 10.7 / 10.3	22 / 20 / 22	36.4 / 27.3 / 27.4
OME-5	500	4430	80	195 / 210 / 208	8.1 / 10.5 / 10.4	30 / 27 / 28	36.4 / 27.3 / 27.4
OME-6	650	5755	80	300 / 203 / 203	12.5 / 10.3 / 10.3	42 / 34 / 34	36.4 / 27.3 / 27.4
OME-7	1000	8855	120	130 / 168 / 165	5.4 / 8.0 / 7.8	50 / 47 / 48	36.4 / 27.3 / 27.4
OME-8	1500	13280	120	190 / 233 / 233	7.9 / 11.0 / 10.9	54 / 53 / 56	36.4 / 27.3 / 27.4

- The running current is measured at max torque.

Explosion-proof Quarter-turn Electric Valve Actuator Electrical Data

1.3 24VAC/DC, Modulating Control, 75% duty cycle

Model	Torque		Motor Power	Power Consumption	Running Current	Running Time	Lock Current
	Nm	in-lb	W	DC / 60 / 50 Hz	DC / 60 / 50 Hz	DC / 60 / 50 Hz	DC / 60 / 50 Hz
				W	Amp	Sec / 90°	Amp
OME-1	35	310	10	32 / 39 / 40	1.3 / 1.9 / 1.9	18 / 12 / 13	2.6 / 2.5 / 2.5
OME-A / AM	50	445	10	32 / 38 / 37	1.3 / 1.9 / 1.8	35 / 23 / 24	2.6 / 2.5 / 2.5
OME-2	90	800	40	46 / 76 / 75	1.9 / 3.4 / 3.4	19 / 15 / 15	14.1 / 10.4 / 10.4
OME-3	150	1330	40	65 / 80 / 87	2.7 / 3.6 / 3.9	30 / 24 / 24	14.1 / 10.4 / 10.4
OME-4	400	3540	80	178 / 211 / 203	7.4 / 10.7 / 10.3	22 / 20 / 22	36.4 / 27.3 / 27.4
OME-5	500	4430	80	195 / 210 / 208	8.1 / 10.5 / 10.4	30 / 27 / 28	36.4 / 27.3 / 27.4
OME-6	650	5755	80	300 / 203 / 203	12.5 / 10.3 / 10.3	42 / 34 / 34	36.4 / 27.3 / 27.4
OME-7	1000	8855	120	130 / 168 / 165	5.4 / 8.0 / 7.8	50 / 47 / 48	36.4 / 27.3 / 27.4
OME-8	1500	13280	120	190 / 233 / 233	7.9 / 11.0 / 10.9	54 / 53 / 56	36.4 / 27.3 / 27.4

- The running current is measured at max torque.

1.4 110 - 120VAC, Floating Control, 75% duty cycle

Model	Torque		Motor Power	Power Consumption	Running Current	Running Time	Lock Current
	Nm	in-lb	W	60 / 50 Hz	60 / 50 Hz	60 / 50 Hz	60 / 50 Hz
				W	Amp	Sec / 90°	Amp
OME-1	35	310	10	47 / 47	0.6 / 0.6	12 / 12	2.5 / 2.3
OME-A / AM	50	445	10	39 / 39	0.5 / 0.5	21 / 21	2.5 / 2.3
OME-2	90	800	40	51 / 51	0.5 / 0.5	16 / 16	3.6 / 3.7
OME-3	150	1330	40	62 / 62	0.6 / 0.6	26 / 25	3.6 / 3.7
OME-4	400	3540	80	382 / 397	3.7 / 3.8	15 / 15	12.7 / 11.7
OME-5	500	4430	80	372 / 381	3.6 / 3.6	21 / 20	12.7 / 11.7
OME-6	650	5755	80	496 / 543	4.8 / 5.2	29 / 27	12.7 / 11.7
OME-7	1000	8855	120	238 / 261	2.3 / 2.5	35 / 35	12.7 / 11.7
OME-8	1500	13280	120	376 / 349	3.6 / 3.3	42 / 41	12.7 / 11.7

- The running current is measured at max torque.

Explosion-proof Quarter-turn Electric Valve Actuator Electrical Data

1.5 110 - 120VAC, Modulating Control, 75% duty cycle

Model	Torque		Motor Power	Power Consumption 60 / 50 Hz	Running Current 60 / 50 Hz	Running Time 60 / 50 Hz	Lock Current 60 / 50 Hz
	Nm	in-lb	W	W	Amp	Sec / 90°	Amp
OME-1	35	310	10	49 / 50	0.6 / 0.6	18 / 17	3.0 / 3.0
OME-A / AM	50	445	10	49 / 49	0.6 / 0.6	33 / 33	3.0 / 3.0
OME-2	90	800	40	51 / 51	0.5 / 0.5	16 / 15	3.6 / 3.7
OME-3	150	1330	40	62 / 62	0.6 / 0.6	26 / 25	3.6 / 3.7
OME-4	400	3540	80	382 / 397	3.7 / 3.8	15 / 15	12.7 / 11.7
OME-5	500	4430	80	372 / 381	3.6 / 3.6	21 / 20	12.7 / 11.7
OME-6	650	5755	80	496 / 543	4.8 / 5.2	29 / 27	12.7 / 11.7
OME-7	1000	8855	120	238 / 261	2.3 / 2.5	35 / 35	12.7 / 11.7
OME-8	1500	13280	120	376 / 349	3.6 / 3.3	42 / 41	12.7 / 11.7

- The running current is measured at max torque.

1.6 110 - 120VAC, Floating Control, 30% duty cycle

Model	Torque		Motor Power	Power Consumption 60 / 50 Hz	Running Current 60 / 50 Hz	Running Time 60 / 50 Hz	Lock Current 60 / 50 Hz
	Nm	in-lb	W	W	Amp	Sec / 90°	Amp
OME-1	35	310	10	82 / 93	0.7 / 0.8	11 / 14	0.7 / 0.7
OME-A / AM	50	445	10	82 / 94	0.7 / 0.8	21 / 27	0.7 / 0.8
OME-2	90	800	40	104 / 124	0.9 / 1.2	18 / 22	1.4 / 1.5
OME-3	150	1330	40	105 / 126	0.9 / 1.2	28 / 34	1.4 / 1.5
OME-4	400	3540	80	250 / 265	2.1 / 2.3	20 / 25	5.5 / 6.0
OME-5	500	4430	80	262 / 268	2.2 / 2.3	27 / 33	5.5 / 6.0
OME-6	650	5755	80	321 / 277	2.7 / 2.4	36 / 42	5.5 / 6.0
OME-7	1000	8855	120	238 / 249	2.0 / 2.2	52 / 61	5.5 / 6.0
OME-8	1500	13280	120	286 / 268	2.4 / 2.3	54 / 64	5.5 / 6.0

- The running current is measured at max torque.

Explosion-proof Quarter-turn Electric Valve Actuator Electrical Data

1.7 110 - 120VAC, Modulating Control, 30% duty cycle

Model	Torque		Motor Power	Power Consumption 60 / 50 Hz	Running Current 60 / 50 Hz	Running Time 60 / 50 Hz	Lock Current 60 / 50 Hz
	Nm	in-lb	W	W	Amp	Sec / 90°	Amp
OME-2	90	800	40	104 / 124	0.9 / 1.2	18 / 22	1.4 / 1.5
OME-3	150	1330	40	105 / 126	0.9 / 1.2	28 / 34	1.4 / 1.5
OME-4	400	3540	80	250 / 265	2.1 / 2.3	20 / 25	5.5 / 6.0
OME-5	500	4430	80	262 / 268	2.2 / 2.3	27 / 33	5.5 / 6.0
OME-6	650	5755	80	321 / 277	2.7 / 2.4	36 / 42	5.5 / 6.0
OME-7	1000	8855	120	238 / 249	2.0 / 2.2	52 / 61	5.5 / 6.0
OME-8	1500	13280	120	286 / 268	2.4 / 2.3	54 / 64	5.5 / 6.0

- The running current is measured at max torque.

1.8 220 - 240VAC, Floating Control, 75% Duty cycle

Model	Torque		Motor Power	Power Consumption 60 / 50 Hz	Running Current 60 / 50 Hz	Running Time 60 / 50 Hz	Lock Current 60 / 50 Hz
	Nm	in-lb	W	W	Amp	Sec / 90°	Amp
OME-1	35	310	10	50 / 51	0.4 / 0.4	11 / 11	0.6 / 0.6
OME-A / AM	50	445	10	38 / 39	0.3 / 0.3	20 / 20	0.6 / 0.6
OME-2	90	800	40	62 / 63	0.3 / 0.3	25 / 24	2.7 / 2.5
OME-3	150	1330	40	62 / 63	0.3 / 0.3	25 / 24	2.7 / 2.5
OME-4	400	3540	80	434 / 460	2.1 / 2.2	14 / 14	7.0 / 7.7
OME-5	500	4430	80	393 / 397	1.9 / 1.9	19 / 19	7.0 / 7.7
OME-6	650	5755	80	413 / 481	2.0 / 2.3	24 / 25	7.03 / 7.7
OME-7	1000	8855	120	266 / 289	1.3 / 1.4	35 / 34	7.0 / 7.7
OME-8	1500	13280	120	393 / 418	1.9 / 2.0	42 / 40	7.0 / 7.7

- The running current is measured at max torque.

Explosion-proof Quarter-turn Electric Valve Actuator Electrical Data

1.9 220 - 240VAC, Modulating Control, 75% Duty cycle

Model	Torque		Motor Power	Power Consumption 60 / 50 Hz	Running Current 60 / 50 Hz	Running Time 60 / 50 Hz	Lock Current 60 / 50 Hz
	Nm	in-lb	W	W	Amp	Sec / 90°	Amp
OME-1	35	310	10	54 / 55	0.4 / 0.4	18 / 18	2.0 / 2.0
OME-A / AM	50	445	10	55 / 55	0.4 / 0.4	30 / 30	2.0 / 2.0
OME-2	90	800	40	62 / 63	0.3 / 0.3	16 / 15	2.7 / 2.5
OME-3	150	1330	40	62 / 63	0.3 / 0.3	25 / 24	2.7 / 2.5
OME-4	400	3540	80	434 / 460	2.1 / 2.2	14 / 14	7.0 / 7.7
OME-5	500	4430	80	393 / 397	1.9 / 1.9	19 / 19	7.0 / 7.7
OME-6	650	5755	80	413 / 481	2.0 / 2.3	24 / 25	7.03 / 7.7
OME-7	1000	8855	120	266 / 289	1.3 / 1.4	35 / 34	7.0 / 7.7
OME-8	1500	13280	120	393 / 418	1.9 / 2.0	42 / 40	7.0 / 7.7

- The running current is measured at max torque.

1.10 220 - 240VAC, Floating Control, 30% Duty cycle

Model	Torque		Motor Power	Power Consumption 60 / 50 Hz	Running Current 60 / 50 Hz	Running Time 60 / 50 Hz	Lock Current 60 / 50 Hz
	Nm	in-lb	W	W	Amp	Sec / 90°	Amp
OME-1	35	310	10	72 / 72	0.3 / 0.3	11 / 13	0.3 / 0.3
OME-A / AM	50	445	10	72 / 72	0.3 / 0.3	20 / 25	0.3 / 0.3
OME-2	90	800	40	94 / 100	0.4 / 0.5	18 / 22	0.7 / 0.8
OME-3	150	1330	40	96 / 102	0.4 / 0.5	28 / 34	0.7 / 0.8
OME-4	400	3540	80	214 / 288	0.9 / 1.3	20 / 24	2.8 / 3.0
OME-5	500	4430	80	262 / 294	1.1 / 1.3	27 / 33	2.8 / 3.0
OME-6	650	5755	80	262 / 288	1.1 / 1.3	33 / 41	2.8 / 3.0
OME-7	1000	8855	120	214 / 254	0.9 / 1.2	52 / 62	2.8 / 3.0
OME-8	1500	13280	120	262 / 288	1.1 / 1.3	54 / 64	2.8 / 3.0

- The running current is measured at max torque.

Explosion-proof Quarter-turn Electric Valve Actuator Electrical Data

1.11 220 - 240VAC, Modulating Control, 30% Duty cycle

Model	Torque		Motor Power	Power Consumption 60 / 50 Hz	Running Current 60 / 50 Hz	Running Time 60 / 50 Hz	Lock Current 60 / 50 Hz
	Nm	in-lb	W	W	Amp	Sec / 90°	Amp
OME-2	90	800	40	94 / 100	0.4 / 0.5	18 / 22	0.7 / 0.8
OME-3	150	1330	40	96 / 102	0.4 / 0.5	28 / 34	0.7 / 0.8
OME-4	400	3540	80	214 / 288	0.9 / 1.3	20 / 24	2.8 / 3.0
OME-5	500	4430	80	262 / 294	1.1 / 1.3	27 / 33	2.8 / 3.0
OME-6	650	5755	80	262 / 288	1.1 / 1.3	33 / 41	2.8 / 3.0
OME-7	1000	8855	120	214 / 254	0.9 / 1.2	52 / 62	2.8 / 3.0
OME-8	1500	13280	120	262 / 288	1.1 / 1.3	54 / 64	2.8 / 3.0

- The running current is measured at max torque.



SUNYEH ELECTRICAL IND. CO., LTD.

No.68, Ln. 854, Sec. 1, Shatian Rd., Dadu Dist.,
Taichung City 432, Taiwan
Tel: +886-4-26985666 Fax: +886-4-26983668
E-mail: service@sunyeh.com



www.sunyeh.com